UTS SINGLE STATIONS

CHARACTERISTICS	UTS 20	UTS 30	UTS 40	UTS 60	SPERRY PC
INTERNALS:					
PROCESSOR (BIT, TYPE)	8, Z8ØA	8, Z8ØA	8, Z8ØA	16,68010	16,8088-2
PROCESSING SPEED (MHz)	4 MHZ 3.072	4 MHz	4 MHZ 3.072		4.77-7.16
GRAPHICS PROCESSOR	4 14123.572	68010	4 PAI2 35/2	68010	4.77-7.10
STD. USER MEMORY (BYTES)		56K		128K	128K
STD. SYSTEM MEMORY	16K	JOK	4ØK	120K	128K
MEMORY EXP. INCREMENTS	IUN	128K	32K	128,512K	128K
MAXIMUM USER MEMORY		256K	64K	2M	640K
SCREEN BYPASS	x	X	X	X	O4DA
SCREEN DIFASS		^	^	^	
MONITOR:					
MONOCROME	x	Х	Х	X	X
LOW RESOLUTION COLOR		^	^		320 X 200
MEDIUM RESOLUTION COLOR				512 X 375	
HIGH RESOLUTION COLOR				312 X 313	640 X 400
AMOUNT OF COLORS				16	256
REVERSE VIDEO	x	x	X	X 70	230
LOW INTENSITY				X	
BLINKING	X	X	X	X	
		X			
PROTECTED FIELDS	Х	X	X	X	
BACKGROUND COLOR VARIATIONS				Х	X
KEYBOARDS:					
UTS 400	Х		Х		
TEXT PROCESSING (TPU)		Х	Х		
TYPEWRITER	Х		Х		
EXPANDED TYPEWRITER	х		Х		
LOW PROFILE EXP. TYPEWRITER	Х	х	Х	X	1
LOW PROFILE TPU		Х	X		
SPERRYLINK		X	X	6. Jr. V	
KATAKANA /	х		Х		
IBM PC COMP, K/B					X
PERIPHERALS:					
PRINTER INTERFACE	RS-232	RS-232	8-BIT	RS-232	RS-232
OPTIONAL PRINT INTERFACE			RS-232		CENTRONICS
MAX AMOUNT OF PRINTERS	1	1	2	2	3
PRINTER TYPE:					
Ø425 (16Ø/4Ø CPS)	Х	X	Х	Х	
Ø431 (55 CPS LETTER)		X	Х	X	X
0789 (640,300 LPM)			X		
0791 (45 CPS LETTER)			X		
Ø797 (8Ø CPS)	х	X	X		
Ø798 (2ØØ CPS)	X	$\frac{x}{x}$	X		
OUTSIDE VENDOR					X
GRAPHICS COLOR PRINTER				MODEL 35	CMA49
PLOTTER				X	> X =>
DISKETTE/DISK INTERFACE		SA 400	8 BIT	SA 400	Х
OPTIONAL DISK INTERFACE				SCSI	
8" DISKETTES (8406)			985K		
5 1/4" DISKETTES (8439)		737K	737K	737K	320, 360K
5 1/4" WINCHESTER DISK		3ØM		3ØM	10M
MAX AMOUNT DISKETTE UNITS		4	4	4	2
MAX AMOUNT DISK UNITS				2	
DOCUMENT READER		FUTURE	Х	FUTURE	
MAGNETIC STRIPE READER	X	X	X	X	
GRAPHICS INPUT TABLET				X	
CONTROL PAGE ACCESS	х	x	X	Х	

-CENT

CHARACTERISTICS	UTS 20	UTS 30	UTS 40	UTS 60	SPERRY PC
COMMUNICATIONS:					
RS-232C INTERFACE	X	Х	X	Х	х
CCITT X.21 INTERFACE	Х	Х	X	X	
UNISCOPE MODE	X	Х	X	X	OPT.
IBM 3270 SNA					OPT.
IBM 3270 BISYNC.	CARTRIDGE				OPT.
TTY		CP/M PLUS	CP/M	CP/M 68K	STD.
MAXIMUM COMM. SPEED	9600	9600	9600	9600	9600
FOREIGN CHARACTER SET	.8	8	8 .	8	
SOFTWARE: LOADABLE CHARACTER SET	X	X	X	X	<u></u>
	UTS 400	UTS3Ø SCS		UTS 400	MCDOC 1 2
OPERATING SYSTEMS	U15 400	CP/M PLUS		CP/M 68	MSDOS 1.2
		CP/M PLUS	CP/M 2.2 CP/M PLUS		CP/M 86
			CP/M PLUS		
SPERRY SOFTWARE:					UCSD-P
EDIT PROCESSOR	<u> </u>	X	v	X	
TEXT PROCESSING UTILITY		X	X	A	
		X	X	V	
FILE TRANSFER UTILITY DISKETTE UTILITY	<u></u>	X	X	X	
CP/M CONVERSION UTILITY		Ŷ	<u>^</u>	X	
8" TO 5 1/4" UTILITY	<u></u>	^	X	^	
•	ļ	X	X	v	
COBOL PASCAL		X	X	X	
			v	K.	FUTURE _
SPERRYLINK (OIS)		X	<u> </u>	<u> </u>	FUTURE -
GKS GRAPHICS		SID.		STD.	
UTS BUSINESS GRAPHICS				Х	
OUTSIDE VENDORS SOFTWARE:			 	(4.2)	
· · · · · · · · · · · · · · · · · · ·					
WORDSTAR		X	<u> </u>	X	X
MAILMERGE		X	<u> </u>	X	X
SUPERCALC		X	X	X	X
dbase II	-	Х	<u> </u>	X	X
LOTUS 1-2-3		X	<u> </u>	X	X
VISICALC		X	X	X	Х
GAMES		Х	<u> </u>	X	X

3/85